



**Hurricane PLJL** The Next Generation of Professional Series Custom Range Hood Inserts is available now in the ProLine Hurricane Insert Series. The Hurricane has been designed from the ground up to be easy to specify and configure, easy to install and most importantly, easy to clean and 100% Stainless Steel, ensure that this insert will perform flawlessly for years.

**Configuration and Dimensions**

Hood Type . . . . .	Insert
<b>15 Inch Depth Available . . . . .</b>	<b>28   34   40   46</b>
28" Dimensions . . . . .	26" W x 15" D x 11.5" H
34" Dimensions . . . . .	32" W x 15" D x 11.5" H
40" Dimensions . . . . .	38" W x 15" D x 11.5" H
46" Dimensions . . . . .	44" W x 15" D x 11.5" H
<b>18 Inch Depth Available . . . . .</b>	<b>28   34   40   46   52   58</b>
28" Dimensions . . . . .	29.75" W x 18.75" D x 11.5" H
34" Dimensions . . . . .	35.75" W x 18.75" D x 11.5" H
40" Dimensions . . . . .	41.75" W x 18.75" D x 11.5" H
46" Dimensions . . . . .	47.75" W x 18.75" D x 11.5" H
52" Dimensions . . . . .	53.75" W x 18.75" D x 11.5" H
58" Dimensions . . . . .	59.75" W x 18.75" D x 11.5" H
<b>21 Inch Depth Available . . . . .</b>	<b>28   34   40   46   52   58</b>
28" Dimensions . . . . .	26" W x 21" D x 11.5" H
34" Dimensions . . . . .	32" W x 21" D x 11.5" H
40" Dimensions . . . . .	38" W x 21" D x 11.5" H
46" Dimensions . . . . .	44" W x 21" D x 11.5" H
52" Dimensions . . . . .	50" W x 21" D x 11.5" H
58" Dimensions . . . . .	56" W x 21" D x 11.5" H

**Features**

Control Type . . . . .	Push Buttons with LED display
Lighting . . . . .	LED

**Ventilation System**

Maximum Air Flow Capacity . . . . .	.600 or 1200 CFM
Speed Levels . . . . .	.4 Speeds
Airflow (Quiet/Low/Med/High) . . . . .	.150/300/450/600 or 300/600/900/1200
Noise Level . . . . .	.53.8 db or 6.0 Sones Max.
Duct Type/Size . . . . .	.Round 6/8
Voltage . . . . .	.110v
Motor . . . . .	.Single or Dual
Filter Type . . . . .	.Stainless Steel Baffle (Dishwasher Safe)
Material . . . . .	.High Quality 430 Stainless Steel
Warranty . . . . .	.3 Year Parts Warranty