










PLFW 520 the PLFW 520 includes high-efficiency stainless steel mesh filters that filter grease, dirt, and unwanted air out of your kitchen. This wall hood will drastically improve your indoor air quality and contribute to a healthy, comfortable lifestyle. With a dual 600 CFM blower, the 520 has enough power for any job in the kitchen. If you don't need all that power, you can adjust it with the push of a button. The LED display control panel with push buttons features blower speed controls – this model has six different speeds! Also on the control panel, you'll find LED lights controls. These are really convenient to brighten your entire cooktop while cooking! And finally, when you're finishing up in the kitchen, after 1-2 months of use, toss your stainless steel mesh filters into your dishwasher. Easy! The 520 provides impressive functionality and looks beautiful in the kitchen.



Configuration and Dimensions
Hood Type
Sizes Available
24" Dimensions 23.25" W x 19.125" D x 7.875" H
30" Dimensions 29.25" W x 19.125" D x 7.875" H
36" Dimensions 35.25" W x 19.125" D x 7.875" H
42" Dimensions
48" Dimensions
Chimney Dimensions: 11.75" (24-36) W or 19.5" (42-48) W x 10.875"
D x 15.75"–30" H (Telescoping with Two Interlocking 15.75" Sleeves)
Features
Control Type Backlit Touch Button with LED Display
LightingLED
Ventilation System
Ventilation System Maximum Air Flow Capacity 600 (24-36") or 1200 (42-48")
-
Maximum Air Flow Capacity 600 (24-36") or 1200 (42-48")
Maximum Air Flow Capacity 600 (24-36") or 1200 (42-48") Speed Levels
Maximum Air Flow Capacity
Maximum Air Flow Capacity 600 (24-36") or 1200 (42-48") Speed Levels
Maximum Air Flow Capacity 600 (24-36") or 1200 (42-48") Speed Levels 6 Speeds Airflow (Quiet/Low/Med/High) 100/200/300/400/500/600 or 200/400/600/800/1000/1200 Noise Level
Maximum Air Flow Capacity .600 (24-36") or 1200 (42-48") Speed Levels .6 Speeds Airflow (Quiet/Low/Med/High) .100/200/300/400/500/600 or 200/400/600/800/1000/1200 Noise Level .48 db or 4 Sones Max Duct Type/Size .Single 6 (24-36") or Dual 10 (42-48") Voltage .110v Motor .Single (24-36") or Dual (42-48")
Maximum Air Flow Capacity .600 (24-36") or 1200 (42-48") Speed Levels .6 Speeds Airflow (Quiet/Low/Med/High) .100/200/300/400/500/600 or 200/400/600/800/1000/1200 Noise Level .48 db or 4 Sones Max Duct Type/Size .Single 6 (24-36") or Dual 10 (42-48") Voltage .110v Motor .Single (24-36") or Dual (42-48") Filter Type .Stainless Steel Mesh (Dishwasher Safe)
Maximum Air Flow Capacity .600 (24-36") or 1200 (42-48") Speed Levels .6 Speeds Airflow (Quiet/Low/Med/High) .100/200/300/400/500/600 or 200/400/600/800/1000/1200 Noise Level .48 db or 4 Sones Max Duct Type/Size .Single 6 (24-36") or Dual 10 (42-48") Voltage .110v Motor .Single (24-36") or Dual (42-48") Filter Type .Stainless Steel Mesh (Dishwasher Safe) Material .High Quality 430 Stainless Steel
Maximum Air Flow Capacity .600 (24-36") or 1200 (42-48") Speed Levels .6 Speeds Airflow (Quiet/Low/Med/High) .100/200/300/400/500/600 or 200/400/600/800/1000/1200 Noise Level .48 db or 4 Sones Max Duct Type/Size .Single 6 (24-36") or Dual 10 (42-48") Voltage .110v Motor .Single (24-36") or Dual (42-48") Filter Type .Stainless Steel Mesh (Dishwasher Safe)